

SC552 STUMP CUTTER



MAXIMUM CUTTING WIDTH. The SC552 reduce the operator's time repositioning the machine with a cutting height of 31" (78.7 cm) above ground and 25" (63.5 cm) below grade. the straight-line cutting dimension allows the operator to cut a 6' (1.8 m) stump without repositioning the machine.



OPERATOR PRESENCE SYSTEM. This user-friendly operator system is intended to help protect the operator and enhance operator safety. If the operator's hand(s) leave the controls for more than one second, the cutter wheel will disengage, come to a stop and the cutter wheel indicator light will go out.



AUXILIARY CONTROL STATION. In narrow jobsite conditions that restrict use of the main control station, the operator can control ground drive and steering functions from this folding station mounted at the front end of the machine.



FOUR-WHEEL DRIVE WITH DIFFERENTIAL LOCK. With power and torques transferred to each of the four wheels, the SC552 is able to traverse in difficult terrain where the operator can engage the differential locks to maintain pulling power during uneven wheel traction path.



MAINTENANCE ACCESSIBILITY. Easy access to daily service points. Other maintenance areas can be reached easily through removable panels.



SMOOTH OPERATION. The exclusive SmartSweep™ control system monitors engine load and provides continuous feedback, resulting in a smooth and consistent cutter wheel sweep rate.

