



STRAIGHTFORWARD CONTROLS. Controls with minimal electrical components, bringing you back to the basics with modern technology.



NARROW FOOTPRINT. This drill is 8.5" (21.6 cm) narrower in width than the next sized drill in the lineup and can get through a 36" (91.4 cm) gate or fit on a narrow trailer with other iobsite essentials.



LOW SOUND LEVELS. Low noise emission levels at the operator's ear of 85 dBa and a guaranteed sound power of 104 dBa make this drill perfect for installing small utilizes in an urban environment with minimal disruption.



MORE POWER. Equipped with a 48 hp (35.8 kW) Kohler engine, this drill offers 1200 ft-lb (1627 Nm) of spindle torque and 7850 lb (3563.9 kg) of thrust/pullback.



**TRACKS.** Tracks offer ideal traction for operation while providing minimal ground disturbance. This track system design allows a forward ground drive speed of 2.8 mph (4.5 km/h), which is 45% faster than the leading competitor.



MULTIPLE ROD OPTIONS. Equip your drill with either a 6' (1.8 m) 1.66" or 1.31" (4.2 cm or 3.3 cm) Firestick® drill rod and save time on the job with 180' (54.9 m) of on-machine rod carrying capacity.













# D8x12 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

#### **GENERAL WEIGHTS AND DIMENSIONS**

Min transport length: 139" (353 cm) Min transport width: 35.5" (90 cm)

Min transport height: 65" (165 cm) Min weight: 6000 lb (2722 kg)

Max weight: 6600 lb (2994 kg) Angle of approach: 18 deg

Angle of departure: 20 deg

Max engine rpm: 2200 rpm

**ENGINE** 

Make and model: Kohler KDI1903 Fuel type: Ultra-low sulfur diesel

Gross horsepower: 48 hp (36 kW)

Aspiration at full engine load: Turbocharged Max fuel consumption: 2.5 gph (9.4 lph) **Emissions rating:** Tier 4 Final (Stage IV)

Max operating angle (fore/aft): 25 deg Max operating angle (left/right): 25 deg

**OPERATIONAL** 

Thrust rod: 7850 lb (3563.9 kg) Pullback rod: 7850 lb (3563.9 kg)

Max carriage speed at max engine rpm - fpm (m/min): 159 fpm (48.5 m/min)

Max spindle torque (max engine rpm) - ft-lb (Nm): 1200 ft-lb (1627 Nm)

Max spindle speed at max engine rpm - (rpm): 182 rpm

Min bore diameter: 2.5" (6.4 cm)

Max ground drive speed at max engine rpm - mph: 2.8 mph (4.5 km/h)

Noise level at operator's ear: 85 dB(A)

Guaranteed sound power engine: 104 dB(A)

# **FLUID CAPACITIES**

Fuel tank: 18 gal (68.1 L)

Hydraulic system: 25 gal (94.6 L)

### **DRILLING FLUID SYSTEM**

Max flow: 9 gpm (34 L/min)

Max pressure: 750 psi (50.2 bar)

**Brand: FMC** 

On board tank capacity: 25 gal

### **FEATURES**

Breakout system: Standard hyd vise

**Drilling lights: Optional** 

Stakedown system: Standard

Strike alert: Standard Remote lockout: Standard Rod greaser: Optional

Wash wand: Optional

## DRILL PIPE OPTION ONE

Drill rod thread: 1.31 Firestick (#200)

Thread type: Firestick (#200)

**Length:** 6" (1.8 m)

Rod diameter: 1.66" (4.2 cm) Joint inside diameter: 0.8" (2 cm) Joint outside diameter: 1.88" (4.8 cm)

Weight: 26 lb (11.8 kg) Bend radius: 57' (17 m)

Total machine rod capacity: 180' (55 m)

## DRILL PIPE OPTION TWO

Drill rod thread: 1.66 Firestick (#200)

Thread type: Firestick (#200)

Length: 6' (1.8 m)

Rod diameter: 1.66" (4.2 cm) Joint inside diameter: 0.8" (2 cm) Joint outside diameter: 1.88" (4.8 cm)

Weight: 26 lb (11.8 kg) Bend radius: 95.5' (29.1 m)

Total machine rod capacity: 180' (55 m)

Vermeer

puipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information eneer, the Vermeer logo, Equipped to Do More, InSite, Firestick and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. of Digital Control Inc. © 2017 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle

10/17.200 PN 296431615