

# Shredder DW 3060 K Typ F - BioPower



## Dimensions

|                       |              |
|-----------------------|--------------|
| Chassis               | Steel-tracks |
| Total weight (kg)     | 30000        |
| Length (mm)           | 13300        |
| Width (mm)            | 2800         |
| Height (mm)           | 4000         |
| Transport width (mm)  | 2800         |
| Transport height (mm) | 3286         |
| Transport length (mm) | 10120        |

## Drive

|                       |                      |
|-----------------------|----------------------|
| Engine type           | diesel engine        |
| Make                  | MTU (Daimler) 6R1300 |
| Exhaust level         | EUROMOT IV           |
| Motor power (kW / PS) | 360 / 490            |
| Fuel tank (l)         | 600                  |
| Torque (Nm)           | 2300                 |

## Discharge conveyor rear

|             |      |
|-------------|------|
| Width (mm)  | 1200 |
| Length (mm) | 7000 |

## Roller

|                        |           |
|------------------------|-----------|
| Number of rollers      | 1         |
| Roller Length (mm)     | 3000      |
| Roller Diameter (mm)   | 600 / 800 |
| Roller Speed (min-1)   | 28        |
| Number of roller teeth | 14 - 145  |

## Applications

The shredders of the DW series process waste wood, logs, roots, green waste, biowaste, garbage, bulky and industrial waste, mixed construction waste and much more. For special applications, the DW shredders can be easily combined with other Doppstadt products, such as grinders or screens.

## Advantages

- Maximum efficiency and low operational costs thanks to powerful direct drive
- Use of different tooth sizes and shredding kits in one machine
- Easy set-up for maximum operational safety
- Contaminant resistant fine shredding system „Limiter“ (additional equipment)
- Fine shredding system "Selector" for evenly shaped, fines-free finished goods (additional equipment)

