

Grinder AK 235



Dimensions

Chassis	2-axle-trailer
Total weight (kg)	15000
Length (mm)	12050
Width (mm)	2110
Height (mm)	3050
Transport width (mm)	2110
Transport height (mm)	3100
Transport length (mm)	9230

Drive

Engine type	Dieselmotor
Make	Mercedes-Benz OM 926 LA.E3B/5
Exhaust level	EUROMOT III B
Motor power (kW / PS)	175 / 238
Fuel tank (l)	215
Torque (Nm)	850 Nmn at 1200-1600 rpm

Discharge conveyor rear

Width (mm)	1500
Length (mm)	5250
Belt speed (m/s)	2

Flail drum

Width (mm)	1480
Diameter (mm)	900
Speed (min-1)	1140 - 1320 rpm (depending on engine speed)
Number of Flail teeth	16/28

Applications

The grinders of the DOPPSTADT AK series process green waste, yard waste, biowaste, pre-shredded logs and roots, waste wood and wooden pallets. For special applications, the AK grinders can be combined with other Doppstadt products, such as shredders, screening machines or beet washers (e.g. for the pulping of beets).

Advantages

- Compact construction, contaminant-resistant
- Ideal for smaller companies
- Well-proven grinding principle by DOPPSTADT
- Quickly replaceable tools
- Quick refitting for other materials

