

Grinder AK 635 K



Applications

The grinders of the Doppstadt AK series process green waste, yard waste, biowaste, pre-shredded logs and roots, waste wood and wooden pallets. For special applications, the AK grinders can be combined with other Doppstadt products, such as shredders, screening machines or beet washers (e.g. for the pulping of beets).

Advantages

- Powerful engine
- Contaminant-resistant
- High off-road mobility
- Quick refitting of machine for other materials
- Separate power unit

Dimensions

Chassis	Steel-tracks
Total weight (kg)	32000
Length (mm)	14850
Width (mm)	3000
Height (mm)	4570
Transport width (mm)	3000
Transport height (mm)	3390
Transport length (mm)	10025

Drive

Engine type	diesel engine
Make	Mercedes-Benz OM 502 LA.E3B/1
Exhaust level	EUROMOT III B
Motor power (kW / PS)	480 / 653
Fuel tank (l)	750
Torque (Nm)	3000 Nm at 1300 rpm

Discharge conveyor rear

Width (mm)	1500
Length (mm)	7000
Belt speed (m/s)	2

Flail drum

Width (mm)	1690
Diameter (mm)	1100
Speed (min-1)	970 - 1140 rpm (depending on engine speed)
Number of Flail teeth	36

