

# Turbo Mower

The Turbo Mower Elite, Euro, Open and Pro range offers operators a huge choice of cutting widths at very cost effective prices.

A well designed and constructed range, the Turbo Mower is built with durability and ease-of-use in mind – a low maintenance machine that is simple to operate.

## Key Features

- Choice of cutting widths available
- Front mount options
- 1.3 and 1.5 manual offset
- Hydraulic offset standard on 1.9m and above
- Standard fitted roller and side skids
- Cat II three point linkage mounted
- Over run slip clutch protected
- Now with a 2 year warranty



Want to know more about the Turbo Mower range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/flail-mowers-and-toppers/turbo-mower/>



### Adjustable guards

On some models the rear hood can be opened.



### Compact models

Machines for tractors over 800kg and above 30HP.



### Twin head stock

Front and rear mount options available.

## Product Specification

● Standard ○ Optional — Not Available

Turbo Mower	ELITE 130	ELITE 150	ELITE 190	ELITE 225	ELITE 245	ELITE 270	OFFSET 160	OFFSET 225
Working Width	1.3m / 4'3"	1.45m / 4'9"	1.9m / 6'4"	2.26m / 7'5"	2.42m / 8'	2.72m / 8'10"	1.6m / 5'3"	2.25m / 7'4"
Overall Width	1.47m / 4'10"	1.63m / 5'4"	2.1m / 6'10"	2.45m / 8'	2.6m / 8'6"	2.9m / 9'6"	1.8m / 6'	2.45m / 8'
Weight	213kg / 469lbs	237kg / 522lbs	451kg / 994lbs	554kg / 1221lbs	596kg / 1313lbs	632kg / 1393lbs	665kg / 1466lbs	775kg / 1709lbs
Hydraulic Offset	—	—	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	—	—	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	2700mm / 9'	3350mm / 11'
PTO speed	540	540	540	540	540	1000	540	540
Front mount	—	—	—	—	—	—	—	—
No. of Flails (Whale Tail)	18	20	24	28	30	34	20	28
Power requirements	30-37hp	35-40hp	45-60hp	55-75hp	65-90hp	75-100hp	47-60hp	80-117hp
Cutting height	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	30-80mm 1 1/4" - 3 1/4"	30-80mm 1 1/4" - 3 1/4"
Roller size	114mm / 4 1/2"	114mm / 4 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"	140mm / 5 1/2"

Turbo Mower	EURO 250	EURO 280	OPEN 250	OPEN 280	PRO 250	PRO 270	PRO 300
Working Width	2.5m / 8'3"	2.8m / 9'2"	2.44m / 8'	2.77m / 9'1"	2.45m / 8'	2.70m / 8'10"	3.00m / 9'10"
Overall Width	2.67m / 8'9"	3m / 9'10"	2.67m / 8'9"	3m / 9'10"	2.73m / 8'11"	2.98m / 9'9"	3.28m / 10'9"
Weight	867kg / 1911lbs	939kg / 2070lbs	859kg / 1893lbs	928kg / 2045lbs	1210kg / 2667lbs	1284kg / 2830lbs	1390kg / 3064lbs
Hydraulic Offset	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated	Hyd Operated
Fully offset left of centre	500mm / 19 1/2"	500mm / 19 1/2"	500mm / 19 1/2"	500mm / 19 1/2"	400mm / 15 1/2"	400mm / 15 1/2"	400mm / 15 1/2"
PTO speed	1000	1000	1000	1000	1000	1000	1000
Front mount	●	●	—	—	●	●	●
No. of Flails (Whale Tail)	28	32	28	32	20	24	26
Power requirements	65-110hp	75-110hp	65-100hp	75-110hp	68-80hp	80-120hp	95-135hp
Cutting height	43-88mm 1 1/4" - 3 1/2"	43-88mm 1 1/4" - 3 1/2"	32-111mm 1 1/4" - 4 1/2"	32-111mm 1 1/4" - 4 1/2"	45-157mm 1 1/4" - 6 1/4"	45-157mm 1 1/4" - 6 1/4"	45-157mm 1 1/4" - 6 1/4"
Roller size	170mm / 6 3/4"	170mm / 6 3/4"	170mm / 6 3/4"	170mm / 6 3/4"	220 / 8 1/2"	220 / 8 1/2"	220 / 8 3/4"



### Offset mower

Capable of being fully offset and cutting within the width of the tractor. Cutting angles vertical 90° and down 65°.

